

# CANNON™ GHRL

GHRL UL844 listed lighting is designed for oil and gas, mining, metal processing and other environments with flammable and ignitable elements. Optional LiFePO4 battery providing 90-minute runtime for emergency applications.

CLASS I DIV. 2

CLASS II DIV. 1

CLASS II DIV. 2

CLASS III



## KEY FEATURES



- A EASY INSTALLATION.** Single barrel nut and hinge design, one-hand operation for quick and easy installation
- B LOW PROFILE.** 196mm in height with maximum 32,000 lumen output fits perfectly for mounting in confined areas.
- C HIGH EFFICACY.** Lumens efficacy up to 170Lm/W, reducing energy costs by up to 75% over conventional lamps.
- D RETROFIT FRIENDLY.** Universal mounting accessories minimizes the SKUs and maximizes the flexibility.
- E BUILD TO LAST.** Copper-free aluminum housing and impact resistant lens sealed from the outside environment provides ingress protection against water and dust.
- F EXPANDABILITY.** Sensor can be attached on the light to realize the intelligent application.

## 7 MOUNTING OPTIONS



# HAZLOC EMERGENCY HIGH BAY LIGHTING

## CLASSIFICATIONS

### NEC/CEC Standard

- UL 844 Hazardous Locations
  - Class I Division 2, Group A, B, C, D
  - Class II Division 1, Group E, F, G
  - Class II Division 2, Group F, G
  - Class III
  - Class I, Zone 2, Group IIC
  - Zone 21, Zone 22

- UL 924
- UL 1598 Wet Locations
- UL 8750 LED Safety
- CSA C22.2 No.137
- CSA C22.2 NO. 250.0

## TECHNICAL DATA

### ELECTRIC & OPTICAL

Rated Power	40W / 60W / 80W / 100W
Input Voltage	AC100-277V
Input Frequency	50/60Hz

### EMERGENCY BACK-UP

Emergency Power	15W
Lumen Output	≥2,400lm
Recharging time	24 hours
Rated autonomy	≥90 mins

### OPTICAL

Lumen Output	13,600lm ~ 32,000lm
Luminous Efficacy	160 - 170Lm/W
Beam Angle	T1, T3, 110°
Color Temperature	Amber 2700K 3000K 4000K 5000K
CRI	Ra>70

### ENVIRONMENTAL & TECHNICAL

Ambient Temperature	-20°C~+50°C
Ambient Humidity	10%~90% RH
Lens Material	Glass / PC / Drop lens
Mounting Options	Pendant / Ceiling / Wall mount / Stanchion / U-Bracket
Cable Entries	3/4" NPT, 1-1/4" NPT, 1-1/2" NPT
Net Weight	8Kg

## OPTIONS AND WARRANTY

- Glass lens standard, PC, drop lens options
- Wire guard
- Safety cable
- Dark sky visor
- 10kV surge protector is standard, 20kV is optional
- 1-10V dimming capabilities
- L70 > 150,000 operation hours@ 25°C
- 5-year limited system warranty