


# DICE™ GHCP

GHCP series canopy lights are designed with a squared shape for petrol pump and gas stations. Standard Hazardous Location Listings include Class I, Division 2, Groups A, B, C, D. approved.

CLASS I DIV. 2




## KEY FEATURES



- A BUILD TO LAST.** Durable stainless steel housing, Copper-free aluminum heat sink, impact-resistant glass lens. Corrosion, vibration, impact and shock resistant.
- B MODULAR DESIGN.** provides 2 models with light output ranging from 7,500 lumens up to 22,500 lumens.
- C HIGH EFFICACY.** Lumens efficacy up to 150Lm/W, reducing energy costs by up to 75% over conventional lamps.
- D LOW PROFILE.** Low profile & lightweight design is perfect for mounting in confined or low height areas.
- E EASY MOUNTING.** Adjustable swing-out mounting brackets standard.

## 4 Mount Options



Surface mount

Recessed mount

Hanging mount

Pendant mount

# HAZARDOUS LOCATION CANOPY LIGHTING

## COMPLIANCES

### NEC/CEC Standard

UL 844 Hazardous Locations  
Class I Division 2, Group A, B, C, D  
Class I, Zone 2, Group IIC  
Simultaneous Presence

CSA C22.2 No.137-18  
CSA C22.2 NO. 141-15  
UL 1598 Wet Locations  
UL 8750 LED Safety  
UL/cUL Listed Pending\*

IP66  
IK08

## TECHNICAL DATA

### ELECTRIC & OPTICAL

Rated Power	75W / 150W
Input Voltage	AC100-277, 347-480V
Lumen Output	7,500lm ~ 22,500lm
Luminous Efficacy	150Lm/W
Beam Angle	60° / 90° / 110°
Color Temperature (CCT)	2700K 3000K 4000K 5000K

### ENVIRONMENTAL & TECHNICAL

Ambient Temperature	-40°C~+50°C
Operating Humidity	10%~90% RH
Lens Material	Glass
Mounting Options	Recessed / Surface / Hanging Pendant mount
Net Weight	6kg

## OPTIONS AND ACCESSORIES

- Safety cable
- Transparent or frosted glass
- 10kV surge protector is standard, 20kV is optional
- 1-10V dimming capabilities
- 2 different surface mount options
- L70:150,000 hours@ 50°C
- 5-year limited system warranty